

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
1 April 2004 (01.04.2004)

PCT

(10) International Publication Number
WO 2004/026437 A1

(51) International Patent Classification⁷: **B01D 35/147**,
35/30, 29/15

NTZ Nederland BV, Sydneystraat 60, NL-3047 BP Rotterdam (NL). **BORGER, Ron** [NL/NL]; NTZ Nederland BV, Sydneystraat 60, NL-3140 AA Rotterdam (NL).

(21) International Application Number:
PCT/IB2003/004079

(81) Designated States (*national*): AU, BR, CN, IN, JP, KR, MX, US.

(22) International Filing Date:
19 September 2003 (19.09.2003)

(84) Designated States (*regional*): European patent (BE, DE, DK, ES, FR, GB, IT, NL, SE).

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
02078889.9 19 September 2002 (19.09.2002) EP

Declarations under Rule 4.17:

- as to the identity of the inventor (Rule 4.17(i)) for the following designations AU, BR, CN, IN, JP, KR, MX, European patent (BE, DE, DK, ES, FR, GB, IT, NL, SE)
- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AU, BR, CN, IN, JP, KR, MX, European patent (BE, DE, DK, ES, FR, GB, IT, NL, SE)
- of inventorship (Rule 4.17(iv)) for US only

(71) Applicant (for all designated States except US): **NTZ NEDERLAND BV** [NL/NL]; P.O. Box 25, Sydney straat 60; 3047 BP ROTTERDAM, NL-3140 AA Maassluis (NL).

Published:


- with international search report

(72) Inventors; and

(75) Inventors/Applicants (for US only): **NIEWLAND, Pierre, Gerard** [NL/NL]; P.O. Box 25, NL-3140 AA Maasland (NL). **SCHAERLAECKENS, Willy** [NL/NL];

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: MICRO FILTER DEVICE FOR AN IN LINE FILTERING CONFIGURATION



(57) Abstract: Oil Filtering device (1) comprising a micro filtration filter element (20, 22) having micro-filtration means (20), and comprising a filter housing (16) and a lid part (17) of said housing (16), tightening means (10) for pressurised interconnection of said lid (17) and housing, the device comprising an oil inlet port (3) and an oil outlet port (9) in connection with a cylindrical interior space (21) of said filter par (5; 20). The filtering device is provided with a by pass means (25, 28) formed by an aperture (28) such as a bore, provided in a closing member (24) for the filtration means, the aperture connecting the space in the device exterior to the filter part to an interior space (21) such that during operation of any system in which the device is incorporated, a minimum flow of oil through the filter device is secured by said by pass means.

BEST AVAILABLE COPY

WO 2004/026437 A1